

DUMPSBOSS.

HCNP-VC (Video Conference)

Huawei H11-861

Version Demo

Total Demo Questions: 15

Total Premium Questions: 303

Buy Premium PDF

<https://dumpsboss.co>

support@dumpsboss.co

support@dumpsboss.co
dumpsboss.co

QUESTION NO: 1

Relationship between the camera and background, Why the background cannot be multifarious. (Select 2 answers)

- A. The AF function of the camera will focus on areas where the edges have high energy. If the background is multifarious, the camera may focus on the background which makes the foreground become vague.
- B. the multifarious background consumes large transmission bandwidth, hampering encoding and decoding effect of the foreground
- C. The AF function of the camera will focus on areas where the edges have high energy. If the background is multifarious, the camera may focus on the foreground which makes the background become vague
- D. the multifarious background consumes large transmission bandwidth, hampering encoding and decoding effect of the background

ANSWER: A B

QUESTION NO: 2

The omnidirectional collect tone suites a big-sized conference room. The omnidirectional collect tone suites a small-sized conference room. ()

- A. TRUE
- B. FALSE

ANSWER: B

QUESTION NO: 3

With network-based recording, the audio and video output of any participants (an audio-only, HD, or telepresence participant) can be recorded. You can play back the recorded contents through the web. ()

- A. TRUE
- B. FALSE

ANSWER: A

QUESTION NO: 4

For Rack MCU, we can configure two main control boards for redundancy backup. On the SMC, you just need to configure one IP address for the active and standby main control boards. ()

- A. TRUE
- B. FALSE

ANSWER: B

QUESTION NO: 5

When you schedule a conference, a message is displayed to indicate insufficient IP port resources. Meanwhile, the MCU used to host the conference is online and has sufficient IP ports. What are the possible causes for this situation. () (Select 2 answers)

- A. No MCU resources are available for the service area.
- B. The license resources are insufficient.
- C. The site protocol and transmission rates do not match.
- D. The MCU has not registered with the GK.

ANSWER: A D

QUESTION NO: 6

For DVI output, VP 9039S and VP 9039A can support the input resolution of 1080p 60 fps of video and presentation. At this time, the resolution of presentation can reach().

- A. 1080P
- B. 7201
- C. 10801
- D. 720P

ANSWER: A

QUESTION NO: 7

The capability exchange information is as follows().

(Select 3 answers)

- A. TCS

- B. TCSA
- C. TCSR
- D. IRR

ANSWER: A B C

QUESTION NO: 8

MCU Video Firewall Mode has advantages, but it also has limitations, such as(). (Select 3 answers)

- A. The MCU supports communication between only two networks. The communication among more than two networks, however, is not supported.
- B. The GEO port must register with a GK. The GE1 port is used only for calls by number
- C. The endpoint at the GE1 side does not support the SiteCall service.
- D. Sites connected through GE1 ports does not support service switchovers.

ANSWER: A C D

QUESTION NO: 9

Video streams sent from the MCU to the recording server can be () on the server. (Select 3 answers)

- A. Live broadcast
- B. Played on demand
- C. Uploaded
- D. Downloaded

ANSWER: A B D

QUESTION NO: 10

Current video communication mainly uses the 4:2:0 sampling. ()

- A. TRUE
- B. FALSE

ANSWER: A

QUESTION NO: 11

For the following technologies used for traversal between public and private networks, no additional network device is required. () (Select 2 answers)

- A. H.460
- B. ALG
- C. Static NAT
- D. SNP

ANSWER: C D

QUESTION NO: 12

One conference allows for up to () groups of continuous presence.

- A. 1
- B. 12
- C. 24
- D. 96

ANSWER: C

QUESTION NO: 13

The sharp and smooth policy is applicable to the H.264 and H.265 protocol. If it is not in the public capabilities, the sharp and smooth policy does not take effect. ()

- A. TRUE
- B. FALSE

ANSWER: B

QUESTION NO: 14

NAT types include ().

(Select 3 answers)

- A. Static NAT

- B. Dynamic NAT
- C. Port mapping
- D. Protocol mapping

ANSWER: A B C

QUESTION NO: 15

H.239:A maximum of 1080i resolution is supported for dual-streams, which is the best dual-stream processing capability in the industry.()

- A. TRUE
- B. FALSE

ANSWER: B