

# DUMPSBOSS.

## Fortinet NSE 7 - Enterprise Firewall 6.0

Fortinet NSE7 EFW-6.0

Version Demo

Total Demo Questions: 5

Total Premium Questions: 30

Buy Premium PDF

<https://dumpsboss.co>

[support@dumpsboss.co](mailto:support@dumpsboss.co)

support@dumpsboss.co  
dumpsboss.co

## QUESTION NO: 1

What does the dirty flag mean in a FortiGate session?

- A. The session must be removed from the former primary unit after an HA failover.
- B. Traffic has been identified as from an application that is not allowed.
- C. The next packet must be re-evaluated against the firewall policies.
- D. Traffic has been blocked by the antivirus inspection.

ANSWER: C

## QUESTION NO: 2

What configuration settings change the behavior for content-inspected traffic while FortiGate is in conserve mode? (Choose two.)

- A. mem-failopen
- B. ips-failopen
- C. utm-failopen
- D. av-failopen

ANSWER: B D

## QUESTION NO: 3

View the exhibit, which contains the output of a BGP debug command, and then answer the question below.

```
FGT # get router info bgp summary
BGP router identifier 0.0.0.117, local AS number 65117
BGP table version is 104
3 BGP AS-PATH entries
0 BGP community entries

Neighbor      V   AS   MsgRcvd  MsgSent  TblVer   InQ  OutQ   Up/Down    State/PfxRcd
10.125.0.60   4 65060   1698     1756     103     0     0    03:02:49    1
10.127.0.75   4 65075   2206     2250     102     0     0    02:45:55    1
100.64.3.1    4 65501   101      115      0       0     0    never       Active

Total number of neighbors 3
```

Which of the following statements about the exhibit are true? (Choose two.)

- A. The local router's BGP state is Established with the 10.125.0.60 peer.

- B. Since the counters were last reset; the 10.200.3.1 peer has never been down.
- C. The local router has received a total of three BGP prefixes from all peers.
- D. The local router has not established a TCP session with 100.64.3.1.

**ANSWER: A D**

## QUESTION NO: 4

View these partial outputs from two routing debug commands:

```
# get router info kernel
tab=254 vf=0 scope=0 type=1 proto=11 prio=0 0.0.0.0/0.0.0.0/0->0.0.0.0/0 pref=0.0.0.0 gwy=10.200.1.254
dev=2(port1)
tab=254 vf=0 scope=0 type=1 proto=11 prio=10 0.0.0.0/0.0.0.0/0->0.0.0.0/0 pref=0.0.0.0 gwy=10.200.2.254
dev=3(port2)
tab=254 vf=0 scope=253 type=1 proto=2 prio=0 0.0.0.0/0.0.0.0/0->10.0.1.0/24 pref=10.0.1.254 gwy=0.0.0.0
dev=4(port3)
# get router info routing-table all
S* 0.0.0.0/0 [10/0] via 10.200.1.254, port1
    [10/0] via 10.200.2.254, port2, [10/0]
C 10.0.1.0/24 is directly connected, port3
C 10.200.1.0/24 is directly connected, port1
C 10.200.2.0/24 is directly connected, port2
```

Which outbound interface will FortiGate use to route web traffic from internal users to the Internet?

- A. Both port1 and port2
- B. port3
- C. port2
- D. port1

**ANSWER: A**

## QUESTION NO: 5

View the exhibit, which contains the output of a debug command, and then answer the question below.

```
# diagnose hardware sysinfo conserve
memory conserve mode: on
total RAM: 3040 MB
memory used: 2706 MB 89% of total RAM
Memory freeable: 334 MB 11% of total RAM
memory used + freeable threshold extreme: 2887 MB 95% of total RAM
memory used threshold red: 2675 MB 88% of total RAM
memory used threshold green: 2492 MB 82% of total RAM
```

Which one of the following statements about this FortiGate is correct?

- A. It is currently in system conserve mode because of high CPU usage.
- B. It is currently in extreme conserve mode because of high memory usage.
- C. It is currently in proxy conserve mode because of high memory usage.
- D. It is currently in memory conserve mode because of high memory usage.

**ANSWER: D**