

# DUMPSBOSS.

## Automating and Programming Cisco Security Solutions (300-735 SAUTO)

Cisco 300-735

Version Demo

Total Demo Questions: 10

Total Premium Questions: 58

Buy Premium PDF

<https://dumpsboss.co>

[support@dumpsboss.co](mailto:support@dumpsboss.co)

support@dumpsboss.co  
dumpsboss.co

## QUESTION NO: 1 - (DRAG DROP)

DRAG DROP

Drag and drop the code to complete the Cisco Umbrella Investigate WHOIS query that returns a list of domains that are associated with the email address "admin@example.com". Not all options are used.

Select and Place:

"https://investigate.api.umbrella.com/ [ ] /		
[ ] /	[ ]	"
email	emails	WHOIS
admin@example.com	whois	{admin@example.com}

ANSWER:

"https://investigate.api.umbrella.com/ WHOIS /		
emails	/	admin@example.com "
email	emails	WHOIS
admin@example.com	whois	{admin@example.com}

Explanation:

<https://docs.umbrella.com/investigate-api/docs/whois-information-for-a-domain-1>

## QUESTION NO: 2

What are two capabilities of Cisco Firepower Management Center eStreamer? (Choose two.)

- A. eStreamer is used to get sources for intelligence services.
- B. eStreamer is used to send malware event data.
- C. eStreamer is used to get a list of access control policies.

- D. eStreamer is used to send policy data.
- E. eStreamer is used to send intrusion event data.

**ANSWER: B E**

### QUESTION NO: 3

Which two event types can the eStreamer server transmit to the requesting client from a managed device and a management center? (Choose two.)

- A. user activity events
- B. intrusion events
- C. file events
- D. intrusion event extra data
- E. malware events

**ANSWER: B D**

### QUESTION NO: 4

After changes are made to the Cisco Firepower Threat Defense configuration using the Cisco Firepower Device Manager API, what must be done to ensure that the new policy is activated?

- A. Submit a POST to the `/api/fdm/latest/operational/deploy` URI.
- B. Submit a GET to the `/api/fdm/latest/operational/deploy` URI.
- C. Submit a PUT to the `/api/fdm/latest/devicesettings/pushpolicy` URI.
- D. Submit a POST to the `/api/fdm/latest/devicesettings/pushpolicy` URI.

**ANSWER: A**

### QUESTION NO: 5

```
quiz = [  
  {  
    "question": "Which of these is an IEEE standard for port-based Network Access Control",  
    "choices": {"a": "802.11x", "b": "802.1x", "c": "802.11a", "d": "802.11b"},  
    "answer": "b"  
  },  
]
```

Refer to the exhibit.

Which expression prints the text "802.1x"?

- A. `print(quiz[0]['choices']['b'])`
- B. `print(quiz['choices']['b'])`
- C. `print(quiz[0]['choices']['b']['802.1x'])`
- D. `print(quiz[0]['question']['choices']['b'])`

**ANSWER: A**

## QUESTION NO: 6

Which curl command lists all tags (host groups) that are associated with a tenant using the Cisco Stealthwatch Enterprise API?

- A. `curl -X PUT "Cookie:{Cookie Data}"https://{stealthwatch_host}/smc-configuration/rest/v1/tenants/{tenant_id}/tags`
- B. `curl -X POST -H"Cookie:{Cookie Data}"https://{stealthwatch_host}/smc-configuration/rest/v1/tenants/tags`
- C. `curl -X GET -H"Cookie:{Cookie Data}"https://{stealthwatch_host}/smc-configuration/rest/v1/tenants/{tenant_id}/tags`
- D. `curl -X GET -H"Cookie:{Cookie Data}"https://{stealthwatch_host}/smc-configuration/rest/v1/tenants/tags`

**ANSWER: C**

## QUESTION NO: 7

Which two commands create a new local source code branch? (Choose two.)

- A. `git checkout -b new_branch`
- B. `git branch -b new_branch`
- C. `git checkout -f new_branch`
- D. `git branch new_branch`

E. git branch -m new\_branch

**ANSWER: A D**

**Explanation:**

```
Content-Type: application/json
Accept: application/json
Authorization: Bearer <api_key>
```

```
Content-Type: application/json
Accept: application/json
Authorization: ApiKey <username>:<api_key>
```

```
Content-Type: application/json
Accept: application/json
Authorization: Basic <api_key>
```

```
Content-Type: application/json
Accept: application/json
Authorization: <username>:<api_key>
```

**QUESTION NO: 8**

Which two URI parameters are needed for the Cisco Stealthwatch Top Alarm Host v1 API? (Choose two.)

- A. startAbsolute
- B. externalGeos
- C. tenantId
- D. intervalLength
- E. tagID

**ANSWER: C E**

**QUESTION NO: 9**

Request URL:

`https://198.18.133.8/api/fdm/v1/policy/intrusionpolicies`

Refer to the exhibit.

What is the purpose of the API represented by this URL?

- A. Getting or setting intrusion policies in FMC
- B. Creating an intrusion policy in FDM
- C. Updating access policies
- D. Getting the list of intrusion policies configured in FDM

**ANSWER: D**

## QUESTION NO: 10 - (DRAG DROP)

DRAG DROP

Drag and drop the code to complete the URL for the Cisco AMP for Endpoints API POST request so that it will add a sha256 to a given file\_list using file\_list\_guid.

Select and Place:

`https://api.amp.cisco.com/v1`

/  /  /  /

files	file_lists
{:sha256}	{:file_list_guid}

**ANSWER:**



## Explanation:

Reference:

[https://api-docs.amp.cisco.com/api\\_actions/details?api\\_action=POST+%2Fv1%2Ffile\\_lists%2F%7B%3Afile\\_list\\_guid%7D%2Ffiles%2F%7B%3Asha256%7D&api\\_host=api.eu.amp.cisco.com&api\\_resource=File+List+Item&api\\_version=v1](https://api-docs.amp.cisco.com/api_actions/details?api_action=POST+%2Fv1%2Ffile_lists%2F%7B%3Afile_list_guid%7D%2Ffiles%2F%7B%3Asha256%7D&api_host=api.eu.amp.cisco.com&api_resource=File+List+Item&api_version=v1)