

DUMPSBOSS.

Using HPE OneView

HP HPE2-T35

Version Demo

Total Demo Questions: 8

Total Premium Questions: 53

Buy Premium PDF

<https://dumpsboss.co>

support@dumpsboss.co

support@dumpsboss.co
dumpsboss.co

QUESTION NO: 1

An administrator is creating a volume template in HPE OneView to manage storage volumes on an HPE 3PAR StoreServ storage system. In addition to the storage pool and capacity, which parameters in the template must the administrator specify? (Choose two.)

- A. provisioning type
- B. drive type
- C. sharing mode
- D. deduplication method
- E. storage type

ANSWER: A C

QUESTION NO: 2

The administrator has configured Server Profile Templates to use Virtual serial numbers. Where can you go in HPE OneView to see hardware-based serial numbers?

(Choose two.)

- A. Server Profile Templates page
- B. Server Hardware page
- C. Server Profile page
- D. Server Hardware Types page
- E. Reports > Server inventory page.

ANSWER: B C

QUESTION NO: 3

An administrator needs to customize the BIOS and local RAID configuration for a collection of HPE ProLiant servers. What should the administrator use to accomplish this task?

- A. Smart Start Scripting Toolkit
- B. Global Dashboard
- C. server hardware
- D. Server Profile Template

ANSWER: B

QUESTION NO: 4

What permissions are included with the user role: "Server profile architect"? (Choose two.)

- A. delete server profile templates
- B. delete scopes
- C. perform firmware updates
- D. update scopes
- E. create server profile templates

ANSWER: A E

QUESTION NO: 5

After assigning a server profile to an HPE ProLiant blade, you notice that the serial number being reported on the server profile page is not the one that matches the label on the server. You want the reported serial number to match the label. What do you need to do?

- A. Create a new Server Profile and go to the "Advanced" section, then change the radio button for the serial number/UUID from "Virtual" to "Physical" and apply it to the server.
- B. Edit the Server Profile and go to the "Advanced" section, then change the radio button for serial number/UUID from "Virtual" to "Physical".
- C. Create a new Server Profile Template and go to the "Advanced" section, then change the radio button for the serial number/UUID from "Virtual" to "Physical".
- D. Edit the Server Profile and go to the "Advanced" section, then change the radio button for serial number/ UUID from "Virtual" to "Physical" and enter the serial number.

ANSWER: D

QUESTION NO: 6

In addition to the REST client, what is another way to access the HPE REST APIs? (Choose two.)

- A. Native BASH Linux shell
- B. PuTTY client
- C. Windows PowerShell
- D. Unified Extensible Firmware Interface (UEFI)
- E. cURL command line utility

ANSWER: A E

QUESTION NO: 7

Refer to the exhibit.

	Value
Name	ProdNet 100
VLAN ID	100
Type	Tagged

What is the PowerShell command to create an Ethernet Network resource?

- A. Get-HPOVNetwork -Name "ProdNet 100" | New-HPOVServerProfileConnection -ConnectionID 1 -Name "ProdNet 100"
- B. New-HPOVUplinkSet -Name "ProdNet 100" -Networks (Get-HPOVNetwork -Name "ProdNet100")
- C. New-HPOVNetwork -Name "ProdNet 100" -VlanId 100
- D. New-HPOVNetworkSet -Name "ProdNet 100"

ANSWER: C

QUESTION NO: 8

Before applying server profiles to a group of servers, what is the first thing you should check?

- A. The servers are all the same hardware type.
- B. The servers have the correct firmware installed.
- C. The servers are powered down.
- D. The servers are all Synergy compute modules.

ANSWER: A