

DUMPSBOSS.

CIW JavaScript Specialist

CIW 1D0-735

Version Demo

Total Demo Questions: 10

Total Premium Questions: 55

Buy Premium PDF

<https://dumpsboss.co>

support@dumpsboss.co

support@dumpsboss.co
dumpsboss.co

QUESTION NO: 1

Consider the following code:

```
1 <script type="text/javascript">
2 function changeOption(){
3     alert(document.myForm.mySelectBox.value);
4 }
5 </script>
6 <form name="myForm">
7 <select name="mySelectBox">
8 <option>First Option</option>
9 <option>Second Option</option>
10 <option>Third Option</option>
11 </select>
12 <input type="submit" value="Submit" />
13 </form>
```

Charies wants to write code to execute the changeOption function after the user chooses an option in the select menu. What change to the code should he make?

- A. Change line 7
- B. Change line 2 to function changeOption (onchange){
- C. Change line 6 to
- D. Change line 6 to

ANSWER: A

QUESTION NO: 2

Consider the following code:



Which of the following is true based on the above code?

- A. The function sofaPic will be called upon when sofaPic image loads
- B. The function sofaPic is called when the image fails to load

- C. The function sofaPic is called when the mouse pointer moves off the image
- D. The function sofaPic is called when the mouse pointer moves over the image

ANSWER: B

QUESTION NO: 3

Consider the following code:

```
<!DOCTYPE html>
<html>
<head>
<title>Join our Mailing List</title>
<meta charset="utf-8" />
</head>
<body>
<script type="text/javascript">
function processForm(){ alert("Form Submitted"); }
</script>
<form name="myForm">
First Name: <input type="text" name="firstName" />
Email: <input type="text" name="email" />
<input type="submit" value="Submit" />
</form>
</body>
</html>
```

The processform() function is not executed when the submit button is pressed. What change should be made to correct this?

- A. The onsubmit event handler should be added to the tag.
- B. The onsubmit event handler should be added to the tag.
- C. The onfocus event handler should be added to the tag.
- D. The onfocus event handler should be added to the tag.

ANSWER: A

QUESTION NO: 4

Consider the following code:

```

<body>
<h1>Computer Inventory</h1>
<h4>Click the button each time a computer is sold to update inventory.</h4>
<button type="button" onclick="updateInventory()">Update Inventory</button>
<h4 id="stock">20</h4>

<script type="text/javascript">
var inventory = (function () {
    var inStock = 20;
    return function () {return inStock -= 1;}
})();

function updateInventory(){
    document.getElementById("stock").innerHTML = inventory();
}
</script>
Computers remaining in inventory.
</body>

```

What will be displayed for the computer inventory after the Update Inventory button is clicked twice?

- A. 18
- B. 19
- C. 20
- D. 22

ANSWER: C

QUESTION NO: 5

Consider the following code:

```

1  <script type="text/javascript">
2  function supportTicket(date, name, email, item, description){
3      this.date = date;
4      this.name = name;
5      this.email = email;
6      this.item = item;
7      this.description = description; }
8  var ticket1 = new supportTicket("2017-06-05", "Ryan Nuen", "ryan.nuen@ciwcertified.com", "GTQ6741", "The computer
will not connect to the Internet.");
9  supportTicket.prototype.resolved = false;
10 var ticket2 = new supportTicket("2017-06-06", "Eliza Cruke", "eliza.cruke@ciwcertified.com", "GTQ3561", "I need
the network printer in office 203 installed on my computer.");
11 </script>

```

What does line 9 do?

- A. Nothing it must written as supportTicket. prototype, this, resolve = resolve ; to add the properly resolved to the custom supportTicket object
- B. it add the property resolved to the original instantiated custom supportTicket object ticket1.
- C. it add the property resolved to the newly instantiated custom supportTicket object ticket1.

D. it add the property resolved to all instances instantiated custom supportTicket object ticket1 and ticket2.

ANSWER: B

QUESTION NO: 6

Jackson was testing his code when the Web browser became locked and he had to close it to stop the script What might he have accidentally done when coding his Web site?

- A. Coded an infinite loop
- B. Coded a frame that breaks the same origin policy
- C. Coded an input element that is vulnerable to XSS
- D. Coded deprecated HTML

ANSWER: D

QUESTION NO: 7

Consider the following code:

```
<script type="text/javascript">
var myString = "Dear John";
alert(myString.substring(2, 6));
</script>
```

What text will display in the alert dialog box?

- A. Ear J
- B. Ar Jo
- C. Ear Jo
- D. Ar J

ANSWER: D

QUESTION NO: 8

Which of the following statements is an advantage of using JavaScript on the server-side?

- A. Server-side validation conserves more bandwidth than client-side validation
- B. Server-side JavaScript runs the script on the server, thus eliminating compatibility problems with client-side browsers

- C. Server-side JavaScript requires less processing power on the server level than client-side JavaScript
- D. Server-side JavaScript results in a higher level of end-user satisfaction

ANSWER: A

QUESTION NO: 9

Which script will display Congratulations, you won! In the browser when the script is run?

A)

```
<script type="text/javascript">
var congrats1 = "Congratulations, ";
var congrats2 = "you won!";
document.write(congrats1 + congrats2);
</script>
```

B)

```
<script type="text/javascript">
var congrats1 = "Congratulations, ";
var congrats2 = "you won!";
windows.write(congrats1 + congrats2);
</script>
```

C)

```
<script type="text/javascript">
var congrats1 = "Congratulations, ";
var congrats2 = "you won!";
document.prompt(congrats1 + congrats2);
</script>
```

D)

```
<script type="text/javascript">
var congrats1 = "Congratulations, ";
var congrats2 = "you won!";
alert.document(congrats1 + congrats2);
</script>
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

ANSWER: B

QUESTION NO: 10

Consider the following code.

```
<input id="age" value="0" />
<button onclick="ageTest()">Enter your age.</button>
<p id="test"></p>

<script type="text/javascript">
function ageTest() {
  var age, test;

  age = document.getElementById("age").value;

  test = (age >= 25) ? "You are old enough":"You are not old enough";
  document.getElementById("test").innerHTML = test + " to rent a car from our car rental agency.";
}
</script>
```

Which of the following will occur if the user's response is 25?

- A. The response will not be tested due to an error in the line containing the conditional operator.
- B. The statement "You are not old enough to rent a car from our car rental agency " will be displayed.
- C. The statement "You are old enough to rent a car from our car rental agency " will be displayed.
- D. The statement "You are not old enough" will be displayed in an alert box.

ANSWER: D