

DUMPSBOSS.

Nokia 5G Packet Core Architecture

Nokia 4A0-M10

Version Demo

Total Demo Questions: 5

Total Premium Questions: 40

Buy Premium PDF

<https://dumpsboss.co>

support@dumpsboss.co

support@dumpsboss.co
dumpsboss.co

QUESTION NO: 1

Which 5GS network function allows UE connectivity to 5GC through non-3GPP access networks?

- A. SEPP
- B. N3IWF
- C. NWDAF
- D. NEF

ANSWER: C

QUESTION NO: 2

An AMF needs to know when an SMF deregisters with the NRF. Which of the following NRF APIs should the AMF use?

- A. Nnrf_NFManagement_NFUpdate Request
- B. Nnrf_NFDiscovery_NFDiscover Request
- C. Nnrf_NFManagement_NFStatusSubscribe Request
- D. Nnrf_NFManagement_NFDeregister Request

ANSWER: A

Explanation:

Reference:

https://www.etsi.org/deliver/etsi_ts/123500_123599/123502/15.03.00_60/ts_123502v150300p.pdf

QUESTION NO: 3

In which of the following scenarios is the Service Request procedure performed?

- A. A deregistered UE needs to register with the network.
- B. A registered UE receives a paging request from the network.
- C. A registered UE needs to establish a new PDU session.
- D. A deregistered UE needs to connect to the network using non-3GPP access.

ANSWER: C

QUESTION NO: 4

Which of the following statements about Option 3X dual connectivity is FALSE?

- A. VoLTE traffic is handled by the LTE network.
- B. Dual connectivity is used for high throughput services such as eMBB.
- C. When NR radio quality becomes sub-optimal, gNB decides to split the bearer.
- D. Both eNB and gNB are connected with S1-U interfaces to SGW.

ANSWER: A

QUESTION NO: 5

Which of the following 5GS reference points is used for control plane signaling?

- A. N3
- B. N4
- C. N6
- D. N9

ANSWER: A